

----- MATERIAL SAFETY DATA SHEET -----

BonaKemi

HARDWOOD DRIFAST(TM) QUICK DRY SEALER

Material Safety Data Sheet Bone K(R) MSDS #: 90007
 24-Hour Emergency Telephone Number
 1-800-424-9300 (Chemtrec)

MSDS #: 90007
 DATE OF PREPARATION: 4/30/2001
 LAST REVISION DATE: 4/30/2001

HMIS Ratings:
 HEALTH: 2
 FLAMMABILITY: 2
 REACTIVITY: 0
 PROTECTION: G

----- SECTION I - PRODUCT IDENTIFICATION -----

PRODUCT NAME: DRIFAST(TM) QUICK DRY SEALER
 PRODUCT DESCRIPTION: SOLVENT BASED QUICK DRY/SANDING SEALER
 FOR BARE WOOD FLOORS

----- SECTION II - HAZARDOUS INGREDIENTS -----

INGREDIENT	CAS#	% WEIGHT	Occupational Exposure Limits		VAPOR PRESSURE- mm Hg
			ACGIH-TLV	OSHA-PEL	
STODDARD SOLVENT	8052-41-3	61-64	100 PPM	500 PPM	2.00 @ 20C

----- SECTION III - PHYSICAL DATA -----

BOILING RANGE: 300F-320F (149-160C)
 EVAPORATION RATE: Slower than n-Butyl Acetate
 % VOLATILE - WT: 63
 DENSITY: 7.29 LBS/GAL (0.87KG/L)
 VAPOR DENSITY: Heavier than air
 SOLUBILITY IN WATER: Insoluble
 PRODUCT CHARACTERISTICS: Thin liquid with solvent odor.
 Color varies with product.

----- SECTION IV - FIRE AND EXPLOSION HAZARD DATA -----

FLAMMABILITY CLASSIFICATION: OSHA - Combustible Liquid Class II
 FLASH POINT: 103F (39C) PMCC
 % OF VOL. OF FLAMMABLE LIMITS (Upper): 6.00
 (Lower): 1.0 (for Stoddard Solvent)
 EXTINGUISHING MEDIA: Foam, Carbon Dioxide, Dry Chemical.
 Water may be unsuitable as an extinguishing medium, but helpful in keeping adjacent containers cool.
 UNUSUAL FIRE EXPLOSION HAZARDS: Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, other flames and ignition sources at locations distant from material handling point. Extinguish all sources of flame or spark. Keep containers tightly closed when not in use. Closed containers may explode when exposed to extreme heat. DANGER: Rags, steel wool or waste contaminated with this product may spontaneously catch fire. Immediately after each use, place contaminated rags, steel wool or waste in a sealed, water-filled metal container.
 SPECIAL FIREFIGHTING PROCEDURES: See 2000 North American Emergency Response Guidebook - Guide 128. Wear self-contained breathing apparatus with full facepiece operated in pressure demand or other positive pressure mode. Irritating or toxic substances may be emitted upon thermal decomposition. Avoid breathing vapors.

----- SECTION VI - REACTIVITY DATA -----

STABILITY: Stable
 REACTIVITY WITH WATER: Will Not Occur
 HAZARDOUS DECOMPOSITION PRODUCTS: Usual products of combustion, e.g. Carbon Monoxide, Carbon Dioxide
 HAZARDOUS POLYMERIZATION: Will Not Occur
 INCOMPATIBILITY (MATERIALS TO AVOID): Strong Oxidizers

----- SECTION VII - SPILL OR LEAK PROCEDURES -----

IN CASE MATERIAL IS RELEASED OR SPILLED: Ventilate area and eliminate all ignition sources. Dike or contain spill and absorb with inert absorbent. Prevent spilled material from entering sewers, drains or bodies of water.
 WASTE DISPOSAL: Dispose of contaminated absorbent, container and unused contents in accordance with local, state/provincial and federal regulations.
 SHIPPING INFORMATION: DOT- regulated material only if shipped by air. DOT classification: Paint, 3, UN 1263, PGIII. Exempt for road/rail/ocean under 49 CFR 173.150

----- SECTION VIII - SAFE HANDLING AND USE INFORMATION -----

RESPIRATORY PROTECTION: In areas where TLV is exceeded, use a NIOSH-approved, properly fitted, air-purifying respirator with organic vapor cartridges. In emergency conditions or IDLH (Immediately Dangerous to Life or Health) atmospheres, use a NIOSH-approved, positive pressure, self-contained breathing apparatus or full facepiece airline respirator.

BonaKemi

HARDWOOD DRIFAST(TM) QUICK DRY SEALER

VENTILATION: Use with adequate general and/or local ventilation to maintain exposure level below TLV. Intentional misuse by concentrating and inhaling the contents can be harmful or fatal. Delayed effects from long-term exposure: Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage.

PROTECTIVE GLOVES: Wear chemical-resistant gloves such as nitrile rubber.

EYE PROTECTION: Use chemical splash goggles or OSHA-permitted safety glasses. Have an eyewash station available.

OTHER PROTECTIVE EQUIPMENT: Wear impervious clothing to avoid repeated or prolonged skin contact.

HYGIENIC PRACTICES: Wash hands with soap and water before eating or using rest rooms. Remove and wash contaminated clothing before re-use.

 DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES: Although preparer and owner have taken reasonable care in the preparation of this document, we extend no warranties and make no representation as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each user should make a determination as to the suitability of the information for their particular purpose(s). This MSDS is the most recent received from the product manufacturer or distributor.

COMPAS Code: 57100290

SECTION IX - MISCELLANEOUS

Do not transfer contents to bottles or other unlabeled containers. Do not store in high temperature (above 100F or 38C) environment. Keep from freezing.

KEEP OUT OF THE REACH OF CHILDREN

KEY CODE

- HMIS = Hazardous Materials Information System
- 0 = Minimal Hazard
- 1 = Slight Hazard
- 2 = Moderate Hazard
- 3 = Serious Hazard
- 4 = Severe Hazard
- N/A = Not Applicable
- N/E = Not Established
- ACGIH = American Conference of Governmental Industrial Hygienists
- OEL = Occupational Exposure Limits
- PEL = Permissible Exposure Limit = exposure limit to an airborne contaminant in a workday set by OSHA
- TLV = Threshold Limit Value = Time-weighted average concentration for a normal 8-hour workday without adverse effect.
- IARC = International Agency for Research on Cancer
- NTP = National Toxicology Program
- OSHA = Occupational Safety and Health Administration

For additional health and safety information, call the BonaKemi Compliance Department at (303) 371-1411.

The identities of ingredients are withheld as proprietary information. The information on this data sheet represents our best opinion as to the proper use and handling of this product under normal conditions, based upon information compiled from sources considered to be dependable. It is accurate and reliable to the best of our knowledge and belief, but is not guaranteed to be so. It is the user's responsibility to determine the suitability of this product for a specific purpose and to adopt such safety precautions as may be necessary. Any use of the product which is not in conformance with this data sheet or which involves using the product in combination with any other product or any other process is the responsibility of the user.

BEFORE USING ANY PRODUCT, READ THE LABEL.

BonaKemi U.S.A., Inc. * 14805 E. Moncrieff Place * Aurora, Colorado 80011-1207